



## HUSQVARNA 125B

Efficient hand held blower that combines high blowing power with user friendliness. Perfect for home owners. Well balanced and easy to manoeuvre thanks to in-lined air out let.



### Adjustable tube length

The blowing tube length is adjustable for best performance.




### Cruise control

Fan speed can be set for easier handling.

### Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



### Intuitive controls

The controls are well gathered and easy to access.



## FEATURES

- Auto return stop switch for easy starting
- Air speed cruise control
- Adjustable tube length
- Intuitive controls
- Air purge for easier cold starting
- Easy to operate with in lined air outlet

Technical specifications	
<b>CAPACITY</b>	
Air flow in housing	13.31 m <sup>3</sup> /min
Air flow in pipe	12.03 m <sup>3</sup> /min
Air speed	76 m/s
Air speed (flat nozzle)	76 m/s
Air speed (round nozzle)	58.12 m/s
<b>DIMENSIONS</b>	
Weight	9.4 lbs
Weight	4.26 kg
<b>ENGINE</b>	
Cylinder displacement	28 cm <sup>3</sup>
Electrode gap	0.6 mm
Fuel tank volume	0.5 l
Fuel consumption	575 g/kWh
Maximum power speed	8000 rpm
Power output	0.8 kW
Spark plug	Champion RCJ6Y
<b>EQUIPMENT</b>	
OEM Harness	--
OEM Nozzle type	Round+ Flat
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	107 dB(A)
Sound pressure level at operators ear	94 dB(A)
<b>VIBRATION</b>	
Equivalent vibration level (ahv, eq) handle	11.1 m/s <sup>2</sup>
<b>EXHAUST EMISSIONS</b>	
Exhaust emissions (CO average)	168 g/kWh
Exhaust emissions (HC average)	41.5 g/kWh
Exhaust emissions (NOx average)	0.4 g/kWh

## PXM\_SPAREPARTS



AIR FILTER  
545 11 21-01



CHAINSAWS  
530 09 56-46



545 14 02-01



ROUND NOZZLE 125B, 125BX,  
125BVX  
545 11 80-01



545 08 18-13

SPARKPLUG  
952 03 02-49



530 04 77-21