



HUSQVARNA 372 XP®

A true professional saw in the larger mid-size class, built for very demanding applications. The crankcase and crankshaft are extra heavy-duty and the carburettor has vibration damping in order to handle high speeds and high loads. The saw combines low weight, high power and rapid acceleration with flexible operation. The XP® G model has both heated handles and carburettor.




Quick-release air filter

Facilitates cleaning and replacement of the air filter.




Adjustable oil pump

Adjustable oil pump makes it easy to set the chain lubrication according to your needs.



Air Injection

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



Side-mounted chain tensioner

Side-mounted chain tensioner makes chain adjustment quick and easy.



FEATURES

- Less filter cleanings with Air Injection
- Adjustable chain oil pump
- Quick-release air filter
- Quick and easy chain adjustment
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover

Technical specifications	
DIMENSIONS	
Weight (excl. cutting equipment)	6.3 kg
ENGINE	
Cylinder displacement	70.7 cm ³
Electrode gap	0.5 mm
Fuel consumption	490 g/kWh
Fuel consumption	1.9 kg/h
Fuel tank volume	0.77 l
Idling speed	2700 rpm
Maximum power speed	9600 rpm
Power output	3.9 kW
Spark plug	Champion RCJ7Y, NGK BPMR7A
Torque, max.	4.3 Nm
EQUIPMENT	
Bar mount	Large
Chain speed at max power	21.4 m/s
Chain speed at 133% of maximum engine power speed	28.5 m/s
Pitch	3/8"
Recommended bar length, max	71 cm
Recommended bar length, min	38 cm
Sprocket type	Rim 7
LUBRICANT	
Oil pump capacity Max	20 ml/min
Oil pump capacity Min	4 ml/min
Oil pump type	Automatic
Oil tank volume	0.4 l
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	115 dB(A)
Sound power level, measured	114 dB(A)
Sound pressure level at operators ear	103 dB(A)
VIBRATION	
Equivalent vibration level (ahv, eq) front handle	5.7 m/s ²
Equivalent vibration level (ahv, eq) rear handle	8.0 m/s ²
Material content, other plastics	
Material content, PBT	0.017 kg
Material content, PE	0.018 kg
Material content, PE	0.164 kg
Material content, PP	0.023 kg
Material content, POM	0.121 kg
Material content, silicone rubber	
Material content, nitrile rubber	0.001 kg
Material content, nitrile rubber	0.042 kg
Material content, hydrogenated nitrile rubber	0.009 kg
Material content, fluorosilicone rubber	0.0001 kg
Material content, fluorocarbon rubber	0.026 kg

PXM_SPAREPARTS

AIRFILTER-NYLON 80
575 26 91-01

AIRFILTER-NYLON 44M
575 26 91-02

FELT
503 81 45-03

SPARK PLUG RCJ7Y
503 23 51-08



503 78 72-01



STARTER CORD
501 20 15-02

503 85 95-01

537 01 55-01



FUEL FILTER FOR MOST OF OUR
HANDHELD PRODUCTS
503 44 32-01

503 22 00-01




537 04 41-02




501 68 68-01



503 63 75-02



503 64 78-01



502 52 92-01



REPL. RIM 3/8"X7T
501 59 80-02



503 52 13-03

503 74 44-01



CLUTCH DRUM ASSY
503 93 24-72



503 93 95-71



503 75 22-02



REPL. RIM .325X7T
501 45 74-02

503 81 80-05



AIRFILTER-FELT
575 26 91-03



REPL. RIM 3/8"X8T
505 30 36-61

503 81 80-06