



Husqvarna 395 XP®



Quick-release air filter

Facilitates cleaning and replacement of the air filter.



Adjustable oil pump

Adjustable oil pump makes it easy to set the chain lubrication according to your needs.

Air Injection

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



Magnesium crankcase

Sturdily built crankcase withstands high rpms and tough professional use, ensuring a long service life.



FEATURES

- Less filter cleanings with Air Injection
- Adjustable chain oil pump
- Quick-release air filter
- Magnesium crankcase designed for professional use
- Maximum durability for tough applications
- LowVib® sparing the user's arms and hands

Technical specifications	
DIMENSIONS	
Weight (excl. cutting equipment)	7.9 kg
ENGINE	
Cylinder displacement	94 cm ³
Electrode gap	0.5 mm
Fuel consumption	470 g/kWh
Fuel consumption	2.3 kg/h
Fuel tank volume	0.9 l
Idling speed	2500 rpm
Maximum power speed	8700 rpm
Power output	5.2 kW
Spark plug	Champion RCJ7Y
Torque, max.	5.9 Nm
EQUIPMENT	
Bar mount	Large
Chain speed at 133% of maximum engine power speed	27.7 m/s
Pitch	3/8", .404"
Recommended bar length, max.	90 cm
Recommended bar length, min.	45 cm
Sprocket type	Rim 7
LUBRICANT	
Oil pump capacity Max	20 ml/min
Oil pump capacity Min	15 ml/min
Oil pump type	Automatic
Oil tank volume	0.5 l
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	115 dB(A)
Sound power level, measured	114 dB(A)
Sound pressure level at operators ear	102 dB(A)
VIBRATION	
Equivalent vibration level (ahv, eq) front handle	6.5 m/s ²
Equivalent vibration level (ahv, eq) rear handle	10.2 m/s ²
Basic model	H395XP
Engine Family EPA	JHVXS.0945AD
Approval certificate number	e5*97/68SH3G3*2002/88*0059*00 (I)
Basic model	H395XP
Exhaust emissions (CO average)	263.62 g/kWh
Exhaust emissions (CO FEL)	536 g/kWh
Exhaust emissions (CO average)	771 g/kWh
Exhaust emissions (HC+NOx FEL)	145 g/kWh
Exhaust emissions (HC average)	119.24 g/kWh
Exhaust emissions (NOx average)	1.80 g/kWh
Useful life category	300 hrs
EU type approval	Stage 1
Exhaust emissions (CO average)	417.11 g/kWh
Exhaust emissions (CO average)	714.1 g/kWh
Exhaust emissions (HC average)	123.18 g/kWh
Exhaust emissions (NOx average)	1.06 g/kWh
Material content, other plastics	0.055 kg
Material content, PBT	0.01 kg
Material content, PE	0.035 kg
Material content, PP	0.066 kg
Material content, POM	0.067 kg
Material content, silicone rubber	0.013 kg
Material content, nitrile rubber	0.015 kg
Material content, hydrogenated nitrile rubber	0.009 kg
Material content, fluorosilicone rubber	0.0001 kg
Material content, fluorocarbon rubber	0.028 kg
Material content, chloroprene rubber	0.016 kg

PXM_SPAREPARTS

AIRFILTER-NYLON 80
537 44 44-02

AIRFILTER-NYLON 44M
537 44 44-03

AIRFILTER-FELT
537 44 44-01

SPARK PLUG RCJ6Y
503 23 51-09



503 13 50-01

503 43 29-03

501 67 32-01

FUEL FILTER FOR MOST OF OUR
HANDHELD PRODUCTS
503 44 32-01




503 22 00-01

503 47 05-01

ANTI VIBRATION SPRING
503 46 85-01

ANTI VIBRATION SPRING
503 46 88-01



ANTI VIBRATION SPRING
503 46 95-01

CARBURATOR GASKET KIT
501 49 48-02

REPL. RIM 3/8"X7T
501 59 80-02

REPL. RIM 404"X7T
501 59 79-02



503 46 37-02

503 70 15-02



RIM SYSTEM 3/8"X7T
503 62 59-03



CLUTCH DRUM
503 62 59-04



503 72 07-02