



Husqvarna CS 10

The CS 10 is a very useful and efficient saw system, thanks to a number of smart solutions. The saw is coupled to our electric wall saws WS 482 HF or WS 440 HF. It can be mounted on both sides of the track, and the wire's direction of rotation is reversible. You can saw both vertically and horizontally. Plus there's no need for water for dry cuts in cases when slurry is a concern.



User-friendly wireless remote control

Together with WS 482 HF or WS 440 HF, you can use a remote control, that has a logical and ergonomic design with a large and clear display, which shows the current performance of the saw.



Highly efficient and flexible

Possible to saw both vertically and horizontally. The saw head can be mounted on either side of the track and the direction of the wire is reversible.

Easy handling

Its compact design makes CS 10 easy to operate, transport and store.



Efficient product fleet

Thanks to compatibility between wall and wire systems.



FEATURES

- Its compact design makes CS 10 easy to operate, transport and store.
- Possible to saw both vertically and horizontally. The saw head can be mounted on either side of the track and the direction of the wire is reversible.
- Together with WS 482 HF or WS 440 HF, you can use a remote control, that has a logical and ergonomic design with a large and clear display, which shows the current performance of the saw.
- Efficient product fleet
- The saw has a flexible design and can easily be mounted on objects like pipes.
- The saw can be installed to cut on the right or the left. This gives great flexibility during installation and when selecting the direction of the cut.

Technical Specifications	
ENGINE	
Motor for wire drive	Electric Wall Saw
Output power with WS 440 HF and PP 440 HF	13 kW
Output power with WS 482 HF and PP 480 HF	19 kW
Output power with WS 482 HF and PP 490	19 kW
Spindle starting torque	160 Nm
CUTTING EQUIPMENT	
Wire speed gear 2, max	24 m/s
DIMENSIONS	
Weight	100 kg
Weight with WS 440 HF	135 kg
Weight with WS 482 HF	138 kg
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	100 dB(A)
Sound power level, measured	99 dB(A)
Sound pressure level at operators ear	86 dB(A)
OTHER	
Direction of rotation	Both directions
Wire configuration in drive unit, min	1 m
Net wire storage capacity	10 m
PACKAGING	
Packaging length	800 mm
Packaging width	1200 mm
Packaging height	1310 mm
Packaging volume	1257.6 dm ³