

WIRE SAWS

Husqvarna CS 2512

**WIRE SPEED GEAR 2, MAX**

25 m/s

OUTPUT POWER WITH PP 455

20 kW

NET WIRE STORAGE CAPACITY

16 m

WEIGHT

150 kg

WIRE SAW CS 2512 Wiresaw

Art nr: 965 15 62-01

CS 2512, in combination with the hydraulic unit PP 455 E, is a powerful and easy to use wire saw. It is compact and mobile for smaller jobs but can also handle very large deep sawing jobs. It can be used for a wide range of applications, both on the ground or mounted on walls. Use it for sawing in steel, concrete and other building materials.

LARGE WIRE MAGAZINE

Although the wire saw is compact it has a large...



FLEXIBLE SETUP

Thanks to modular systems, the wire saws are easy to install. They can be positioned both vertically and horizontally. The motor can be detached for easier transportation.

EASY TRANSPORTATION

Practical collapsible handles and foldable...



ALL SPECIFICATIONS

CS 2512

CS 2512 WIRESAW

965 15 62-01

ENGINE

Motor for wire drive	Hydraulic multiple gear
Output power with PP 455	20 kW
Spindle starting torque	190
Power source	Hydraulic

CUTTING EQUIPMENT

Wire speed gear 1, max	20 m/s
Wire speed gear 2, max	25 m/s

HYDRAULICS

Hydraulic oil flow	65 l/min
Hydraulic pressure, max	230 bar

DIMENSIONS

Weight	150 kg
--------	--------

SOUND AND NOISE

Sound power level, guaranteed (LWA)	95 dB(A)
Sound power level, measured	94 dB(A)
Sound pressure level at operators ear	83 dB(A)

OTHER

Direction of rotation	One direction
Wire configuration in drive unit, min	3.4 m
Net wire storage capacity	16 m

DIAMOND TOOLS

GOLD



DIAMOND WIRES ELITE-WIRE C1200

Coolant
Wet /dry
Number of beads mm
53
Bead diameter mm
10.3 mm
Assembly
Springs + rubber, vacuum ...

GOLD



DIAMOND WIRES ELITE-WIRE C888

Coolant
Wet
Number of beads mm
40
Bead diameter mm
11 mm
Assembly
Spring + rubber, hybrid be...

GOLD



DIAMOND WIRES ELITE-WIRE C1000

Coolant
Wet /dry
Number of beads mm
44
Bead diameter mm
10.3 mm
Assembly
Springs + rubber, vacuum ...

GOLD



DIAMOND WIRES ELITE-WIRE C1000 SPL

Coolant
Wet /dry
Number of beads mm
44
Bead diameter mm
10.3 mm
Assembly
Springs + rubber, vacuum-...

RELATED PRODUCTS AND ACCESSORIES



ELECTRICALLY POWERED HYDRAULIC POWER PACKS PP 455 E

2 variants
Hydraulic oil flow
65 l/min
Hydraulic pressure, max
230 bar
Rated current
63 A
Output power (As rated by t...
25 kW



PLATES AND BRACKETS Anchor plate

Accessory for
Wire saws



PLATES AND BRACKETS Angle bracket, single pulley

Accessory for
Wire saws

PLATES AND BRACKETS Angle bracket, double pulley

Accessory for
Wire saws