



Husqvarna K 1 PACE

K 1 PACE high power battery cutter has the power and performance you expect from equivalent petrol-powered cutters. Equipped with X-Halt™ brake function for operational safety. Ergonomic and user-friendly with low vibrations, optimally balanced machine and zero direct emissions. With built-in connectivity so you can easily monitor machine location, runtime, service intervals and receive wireless updates through FOTA (firmware over the air). Powered by Husqvarna PACE battery system with high power and fast charging for impressive productivity and a well-suited match with our specially designed battery blade range for maximised cutting depth and optimised performance. Suitable for concrete pipes, concrete garden plates, cinder blocks etc.



Zero direct emission

Possible to easily cut indoors, in sensitive areas or urban areas where emission levels might be regulated.



Safe operation

X-Halt™ blade brake function capable of stopping the rotation of the blade in fractions of a second.

Powerful

Power and performance in par with equivalent petrol-powered cutters. With an integrated gearbox for higher torque. For high productivity.



Flexible

Versatile and flexible cutting indoors and outdoors. Integrated wet cutting system or VAC attachment as an accessory for dry cutting enables efficient and flexible dust control.



FEATURES

- Powerful
- Safe operation
- Zero direct emission
- Flexible
- Ergonomic and user-friendly
- High power PACE battery system
- A more sustainable choice
- Built-in connectivity
- Smart battery placement
- In-house developed brushless motor provides a high and consistent torque.
- Perfect balance
- Ergonomic handles
- Easy to change blade/guard position
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To provide the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.

Technical Specifications

EQUIPMENT	
Cutting depth, max	121 mm
Blade diameter, max	314 mm
Arbor diameter	20/25,4 mm
Blade thickness, max	1,8 mm
Peripheral speed, max	59 m/s
DIMENSIONS	
Product size width	233 mm
Product size height	400 mm
SOUND AND NOISE	
Sound power level, measured	112,9 dB(A)
Sound pressure level at operators ear	101,9 dB(A)
VIBRATIONS	
Vibrations left/front handle	2 m/s ²
Vibrations right/rear handle	1,1 m/s ²
PACKAGING	
Packaging length	723 mm
Packaging width	261 mm
Packaging height	460 mm
Packaging volume	86,8 dm ³

ACCESSORIES



HUSQVARNA WT 15i
599 58 23-02



HUSQVARNA B380X PACE
970 49 41-01



HUSQVARNA B750X PACE
970 49 42-01



HUSQVARNA C900X PACE
970 49 50-01



HUSQVARNA C1800X PACE
970 49 51-01



VAC ATTACHMENT
529 57 79-01



BATTERY TRANSPORTATION BOX
531 21 54-02