



Husqvarna K 40

Powerful and reliable air-powered industrial cutter, perfect for use indoors or outdoors with access to compressed air. Featuring a long, slim body, with good weight distribution and fine balance laterally and between the handles. It is a convenient alternative for working outdoors where the air change rate is low, such as in pipeline trenches, in deep foundation sites and on marine docks. Indoors and in dust-sensitive areas, it produces no emissions from oil or exhaust.



Smooth blade stop

Reduces the stop time of the blade when the machine is switched off, which enables you to quickly move on to the next job.



Ergonomic and easy cutting

Efficient cutting with less strain on your body, thanks to its low weight, ergonomic handle and low vibrations.

Perfect for use indoor and at low air change rate places

An air-powered Husqvarna cutter is a natural alternative for working indoors, but it is just as viable outdoors in places where the air-change rate is low, such as in pipeline trenches, in deep foundation sites and on marine docks.



Pneumatic motor lubrication

An oil mist lubricates the motor.



FEATURES

- An air-powered Husqvarna cutter is a natural alternative for working indoors, but it is just as viable outdoors in places where the air-change rate is low, such as in pipeline trenches, in deep foundation sites and on marine docks.
 - Ergonomic and easy cutting
- Smooth blade stop
 - An oil mist lubricates the motor.
 - Cutting building blocks, curbstones and garden pavers.
 - Cutting cast concrete.
 - Regular cutting in floors and walls.

Technical Specifications	
CAPACITY	
Output shaft RPM, max	5400 rpm
Peripheral speed, max	100 m/s
DIMENSIONS	
Article gross weight	13000 g
Article net weight	12000 g
Arbor diameter	25.4 mm
Blade diameter, max	350 mm
Blade flange diameter	105 mm
Blade thickness, max	5 mm
Cutting depth, max	125 mm
Product size height	420 mm
Product size length	685 mm
Product size width	235 mm
Weight	9.9 kg
ENGINE	
Engine cooling	Air
EQUIPMENT	
Source system	PAID
LUBRICANTS	
Engine cooling	Air
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	107 dB(A)
Sound power level, measured	107 dB(A)
Sound pressure level at operators ear	92 dB(A)
VIBRATIONS	
Daily Vibration (Aeqv)	9.5 m/s²
Daily Vibration Exposure (A8)	3.36 m/s²
Daily Vibration Time (Time factor)	1 h
Vibrations left/front handle	9.5 m/s²
Vibrations right/rear handle	5.2 m/s²
PACKAGING	
Packaging length	670 mm
Packaging width	235 mm
Packaging height	425 mm
Packaging volume	66.9 dm³