

WALL SAWS

Husqvarna WS 482 HF

**STARTER BLADE DIAMETER, MAXBLADE DIAMETER, MAX**

1000 mm

1600 mm

MAX SPINDLE TORQUE

230 Nm

CUTTING DEPTH, MAX

730 mm

PRODUCT VARIANT

WALL SAW WS 482 HF 1000 mm blade guard

Art nr: 967 64 67-03

PRODUCT DESCRIPTION

WS 482 HF is a very powerful wall saw for cutting reinforced concrete, brick and other building materials, up to 730 mm thickness. The water-cooled electric motor has an unbeatable power-to-weight ratio. This wall saw can be used for all kinds of openings and sawing including stair, bevel and flush cutting. It's easy to assemble, run and transport making your job more comfortable and faster. WS 482 HF can be combined with CS 10, transforming it into a perfect wire saw, or WSC 40, transforming it into a perfect chain saw to finish corners.

ALL SPECIFICATIONS WS 482 HF	WS 482 HF WALL SAW WS 482 HF W/O BLADE GUARD 967 64 67-01	WS 482 HF WALL SAW WS 482 HF 800 MM BLADE GUARD 967 64 67-02	WS 482 HF WALL SAW WS 482 HF 1000 MM BLADE GUARD 967 64 67-03	WS 482 HF WALL SAW WS 482 HF 800MM 3- PSC BG + 840MM 1- PSC BG 967 64 67-05	WS 482 HF WALL SAW WS 482 HF KIT FOR CS 11 967 64 67-06
ENGINE					
Output shaft RPM, max	1,200 rpm	1,200 rpm	1,200 rpm	1,200 rpm	1,200 rpm
Max spindle torque	230 Nm	230 Nm	230 Nm	230 Nm	230 Nm
Spindle starting torque	230 Nm	230 Nm	230 Nm	230 Nm	230 Nm
Rated current	32 A	32 A	32 A	32 A	32 A
Power source	Corded	Corded	Corded	Corded	Corded
CUTTING EQUIPMENT					
Arbor diameter	60/25.4 mm	60/25.4 mm	60/25.4 mm	60/25.4 mm	60/25.4 mm
Blade diameter, max	1,600 mm	1,600 mm	1,600 mm	1,600 mm	1,600 mm
Blade diameter, min	600 mm	600 mm	600 mm	600 mm	600 mm
Cutting depth, max	730 mm	730 mm	730 mm	730 mm	730 mm
Starter blade diameter, max	1,000 mm	1,000 mm	1,000 mm	800 mm	1,000 mm
TRANSMISSION					
Number of gearbox speeds	2	2	2	2	2
PRODUCT DATA					
Water flow, min	3.5 l/min	3.5 l/min	3.5 l/min	3.5 l/min	3.5 l/min
Water pressure, max	7 bar	7 bar	7 bar	7 bar	7 bar
Water temp at min flow, max	25 °C	25 °C	25 °C	25 °C	25 °C
DIMENSIONS					
Product size length	2,200 mm	2,200 mm	2,200 mm	2,200 mm	2,200 mm

ALL SPECIFICATIONS WS 482 HF	WS 482 HF WALL SAW WS 482 HF W/O BLADE GUARD 967 64 67-01	WS 482 HF WALL SAW WS 482 HF 800 MM BLADE GUARD 967 64 67-02	WS 482 HF WALL SAW WS 482 HF 1000 MM BLADE GUARD 967 64 67-03	WS 482 HF WALL SAW WS 482 HF 800MM 3- PSC BG + 840MM 1- PSC BG 967 64 67-05	WS 482 HF WALL SAW WS 482 HF KIT FOR CS 11 967 64 67-06
Product size width	900 mm	900 mm	900 mm	900 mm	900 mm
Product size height	800 mm	800 mm	800 mm	800 mm	800 mm
Weight (complete product w/o side packed articles)	28 kg	28 kg	28 kg	28 kg	28 kg
Weight saw carriage	3.9 kg	3.9 kg	3.9 kg	-	-
Weight saw unit	29.6 kg	28 kg	29.6 kg	29.6 kg	29.6 kg
SOUND AND NOISE					
Sound power level, guaranteed (LWA)	109 dB(A)	109 dB(A)	109 dB(A)	109 dB(A)	109 dB(A)
Sound power level, measured	108 dB(A)	108 dB(A)	108 dB(A)	108 dB(A)	108 dB(A)
Sound pressure level at operators ear	108 dB(A)	108 dB(A)	108 dB(A)	85 dB(A)	85 dB(A)

DIAMOND TOOLS



WALL SAW BLADES **ELITE-CUT W1620**

Diameter mm
800 mm
Arbor diameter
60 mm



WALL SAW BLADES **ELITE-CUT W1620**

Diameter mm
800 mm
Arbor diameter
60 mm



WALL SAW BLADES **ELITE-CUT W1620**

Diameter mm
800 mm
Arbor diameter
60 mm



WALL SAW BLADES **ELITE-CUT W1620**

Diameter mm
1,000 mm
Arbor diameter
60 mm

RELATED PRODUCTS AND ACCESSORIES



BLADE GUARDS AND COVERS **Blade guard** 4 variants

Accessory for
Wall saws



BLADE GUARDS AND COVERS **One-piece blade guard** 2 variants

Accessory for
Wall saws



BLADE GUARDS AND COVERS **Blade guards for flush cutting** 4 variants

Accessory for
Wall saws



ATTACHMENTS **Blade guard guide**

Accessory for
Wall saws