




HUSQVARNA 525iB

Well-balanced, comfortable and efficient professional battery blower. The machine's low noise level allows you to work in the most public of settings. An easy tap on the keypad starts the machine instantly at all times and the cruise control means full focus on blowing leaves and debris away. The blower also has a boost power mode that gives you a little extra power when needed.



Comfortable working position

Working with harness and eyelet equipped machine gives a comfortable working position.



Brushless motor

High torque to weight ratio for increased efficiency, increased reliability, reduced noise and longer product-life.

Low maintenance

No refilling of fuel, less parts to serve and an electronically controlled drive system means less downtime and low operation costs.



Boost effect

Maximized blowing speed during limited time through easy accessible boost mode.



FEATURES

- Low maintenance
- High torque to weight ratio for increased efficiency and reliability.
- Working with harness and eyelet equipped machine gives a comfortable working position.
- Maximized blowing speed through easy accessible boost mode.
- Superb balance, grip and intuitive keypad gives excellent ergonomics.
- Low total weight through few components and lightweight motor.
- Gear up for nonstop operation
- Allows you to quickly switch the same battery between different product applications and keep working.
- Weatherproof (IPX4) - Use in all weather conditions
- Low noise levels enable longer working hours.
- Cruise controlled blowing speed for optimum handling.
- Best performance in class due to the advanced motor fan design.
- Ergonomic handle with easy access to the controls.
- Smart battery pack position, placed horizontally through the body of the machine.

| Technical Specifications | |
|--|--------------------------|
| BATTERY | |
| Battery | No |
| Battery runtime (free run) with savE activated | 21 min |
| Battery type | Li-Ion |
| Battery voltage | 36 V |
| Number of batteries included | -- |
| CAPACITY | |
| Air flow in housing | 12.8 m ³ /min |
| Air flow in housing | 768 m ³ /h |
| Air flow in pipe | 11.6 m ³ /min |
| Air flow in pipe | 696 m ³ /h |
| Air flow in pipe, boost mode | 13.3 m ³ /min |
| Air flow in pipe, boost mode | 798 m ³ /h |
| Air speed | 48 m/s |
| Air speed, boost mode | 56 m/s |
| Air speed (round nozzle) | 48 m/s |
| Blowing Force | 11 N |
| Blowing Force, boost mode | 14.5 N |
| DIMENSIONS | |
| Article gross weight | 4223 g |
| Article net weight | 2860 g |
| Product size height | 27 cm |
| Product size length | 90 cm |
| Product size width | 12 cm |
| Weight without battery | 2.4 kg |
| ENGINE | |
| Motor type | BLDC (brushless) |
| LUBRICANTS | |
| Power source | Battery |
| Power/fuel type | Battery |
| MATERIALS | |
| Master pack: Paper + Cardboard | 0 g |
| Metal total | 0 g |
| Paper | 3700 g |
| Paper + Cardboard total | 3700 g |
| PE total | 0 g |
| PET total | 0 g |
| Plastic foil | 0 g |
| Plastic rigid | 65 g |
| Plastic total | 65 g |
| PS/EPS/HIPS total | 0 g |
| PACKAGING | |
| Packaging height | 295 mm |
| Packaging length | 640 mm |
| Packaging volume | 55.70 dm ³ |
| Packaging width | 295 mm |
| Quantity in Master pack | 1 |
| SOUND AND NOISE | |
| Sound power level, guaranteed (LWA) | 98 dB(A) |
| Sound power level, measured | 97 dB(A) |
| Sound pressure level at operators ear | 82 dB(A) |
| VIBRATIONS | |
| Daily Vibration (Aeqv) | 0.4 m/s ² |
| Daily Vibration Exposure (A8) | 0.3 m/s ² |
| Daily Vibration Time (Time factor) | 2 h |
| Equivalent vibration level (ahv, eq) rear handle | 0.5 m/s ² |

