




## Husqvarna T525

Husqvarna T525 is a lightweight professional top-handle petrol chainsaw made for lighter pruning and trimming jobs. For use with 10-inch or 12-inch guide bar. Our smallest and lightest tree care petrol chainsaw is an efficient tool whether you're doing part-time or full-time professional pruning tasks. It's easy and convenient to use, powered by a low-emission 27cc X-Torq® engine that delivers the performance you need, when you need it.




### Retained bar nut

The retaining function prevents losing the bar nut.



### Simple Starting

When the stop switch has been used, it is automatically reset to ON to facilitate the next start.



### Belt eyelet

Makes it quick and easy to connect the saw to the climbing harness.



### Side Chain Tensioning

Quickly and easily adjust the chain



## FEATURES

- Quick connection to the climbing harness
- When the stop switch has been used, it is automatically reset to ON to facilitate the next start.
- The retaining function prevents losing the bar nut.
- Quickly and easily adjust the chain
- Easy to maintain with tool-less air filter cover
- Air purge for easier cold starting
- The flip-up tank cap is easy to open.
- Specially-designed engine and starter for easy and fast starting with minimum effort

Technical Specifications	
<b>CAPACITY</b>	
Chain speed at 133% of maximum engine power speed	24.1 m/s
Chain speed at max power	18.1 m/s
Clutch engagement speed (±120)	4200 rpm
Idling speed	2900 rpm
Ignition module air gap	0.4 mm
Maximum power speed	13500 rpm
Power output	1.1 kW
Racing speed lower limit	12500 rpm
Torque, max.	1.28 Nm
Torque, max. at rpm	6000 rpm
<b>CERTIFICATIONS</b>	
Eurotested	Yes
<b>DIMENSIONS</b>	
Article gross weight	4923 g
Article net weight	4063 g
Bar length (inch)	10 in
Bar length	25 cm
Weight (excl. cutting equipment)	2.7 kg
<b>ENGINE</b>	
Cylinder bore	35 mm
Cylinder displacement	27 cm <sup>3</sup>
Cylinder stroke	28 mm
Electrode gap	0.65 mm
Engine Family EPA	*HQZS.0274HF
Ignition module air gap	0.4 mm
Spark Plug	NGK CMR6A
<b>EQUIPMENT</b>	
Bar mount type	HSM
Chain type	S93G
Chainsaw sub-group	Arborists Tree-care chainsaws
Gauge	1.3 mm
Handle type	Standard
Pitch	3/8" mini
Source system	PAID
Sprocket type	Spur
<b>LUBRICANTS</b>	
Fuel consumption	408 g/kWh
Fuel tank volume	0.19 l
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
Oil pump type	Adjustable flow
Oil tank volume	0.17 l
Power/fuel type	Gasoline
<b>MATERIALS</b>	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	3000 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
<b>PACKAGING</b>	
Packaging height	260 mm
Packaging length	480 mm
Packaging volume	43.68 dm <sup>3</sup>
Packaging width	350 mm
Quantity in Master pack	1
<b>EMISSION DATA EPA</b>	
Engine Family EPA	*HQZS.0274HF
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	111 dB(A)
Sound power level, measured	110 dB(A)
Sound pressure level at operators ear	98 dB(A)
<b>VIBRATIONS</b>	

**Technical Specifications**

Daily Vibration (Aeqv)	5.2 m/s <sup>2</sup>
Daily Vibration Exposure (A8)	2.8 m/s <sup>2</sup>
Daily Vibration Time (Time factor)	2.4 h
Equivalent vibration level (ahv, eq) front handle	4.9 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) rear handle	5.2 m/s <sup>2</sup>