

Brushcutters



Asia excl. China

Durable backpack brushcutter developed for the most demanding professional customers. The compact design is ideal for working in slopes and the robust spring dampeners in the frame minimize vibrations. Easy maintenance is achieved through a float carburettor and separate covers for the air filter, cylinder and muffler.


Capacity



Engine

Asia excl. China	
Cylinder displacement	41.5 cm ³
Output shaft power	1.47 kW
Fuel tank volume	1.3 l
Fuel Consumption	612 g/kWh
Maximum power speed	7,500 rpm
Idling speed	2,500 rpm
Maximum rpm output shaft	9,600 rpm
Electrode gap	0.6 mm
Clutch engagement speed (±120)	3,300 rpm
Torque, max.	2.26 Nm
Torque, max. at rpm	5,500 rpm
Spark Plug	Champion RCJ6Y

Product data

Asia excl. China	
	

Brand (Ext. Matl Group)	Husqvarna
-------------------------	-----------

Equipment

Asia excl. China	
Grass blade	Multi 330-2
Harness	Integrated
Saw blade	Not included
Trimmer head	Not included
Handle type	Bullhorn

Dimensions

Asia excl. China	
Tube diameter	26 mm
Weight (excl. cutting equipment)	9 kg
Tube length	1,500 mm

Lubricant

Asia excl. China



Lubricant type (bevel gear)	Mineral grease
-----------------------------	----------------

Transmission

Asia excl. China	
Gear ratio	1.25
Drive gear angle	60 °


Vibration

Asia excl. China	
Equivalent vibration level (ahv, eq) left handle	2.6 m/s ²
Equivalent vibration level (ahv, eq) right handle	2.9 m/s ²

Sound and noise

Asia excl. China	
Sound pressure level at operators ear (LpA)	87 dB(A)
Sound power level, guaranteed (LWA)	108 dB(A)

Control



Connectivity

Not applicable



© Husqvarna AB (publ). All rights reserved. Prices shown are recommended retail prices.

[Cookie policy](#) [Terms of use](#) [Privacy notice](#)
[Imprint](#)

[Contact us](#)

[REACH Article 33
Declaration](#)