



Husqvarna TF 440

A multi-functional and durable petrol driven tiller, quipped with a gear-driven transmission that provides strong performance and efficiency, ensures a productive day's work. It has a robust design, with an integrated power take-off (PTO) to maximize the productivity through less down-time and the possibility to use one single machine for multiple field applications.



Protective bumper

The bumper will protect the engine in use or during transportation. It can also serve as lifting handle.



Wheel kit

The wheel kit allows you to use accessories or move the product in an efficient way.

Gear driven transmission

The gear-driven transmission provides a notable improvement in power and efficiency compared to traditional belt drives. Increasing your daily productivity, making it an important asset for your field operations.

Husqvarna gasoline engine

Powerful and reliable husqvarna gasoline engine.



FEATURES

- Enabling high power and efficiency.
- The wheel kit allows you to use accessories or move the product in an efficient way.
- The bumper will protect the engine in use or during transportation. It can also serve as lifting handle.
- Powerful and reliable husqvarna gasoline engine.
- Adjustable handlebar for best working position.
- Enables use of a wide range of accessories for different farming tasks

Technical Specifications	
CAPACITY	
Net power at preset rpm	3600 rpm
Net power at preset rpm Energy	4.4 kW
Power output	4.4 kW
Rotational speed (min/max) max	133 rpm
Rotational speed (min/max) min	29 rpm
Rotational speed	133 rpm
Cultivator type	Front-tine
Working depth	30 cm
Working width	105 cm
Number of tines	8
Counter-rotating tines	No
DIMENSIONS	
Tine diameter	360 mm
Tyre size	415 mm
Weight (complete product w/o side packed articles)	92 kg
ENGINE	
Cylinder displacement	212 cm ³
Engine brand	Husqvarna
Engine name	Husqvarna Engine
Fuel tank volume	4.2 l
Fuel tank volume	1.11 gal (US)
Motor/engine manufacturer	Weima
Power output	6.0 hp
Net power at preset rpm Energy	4.4 kW
Net power at preset rpm	3600 rpm
Air filter type	Oil bath
Oil tank volume	0.6 l
TRANSMISSION	
Transmission steps forward	4
Transmission steps reverse	2
Transmission type	Direct Clutch
EQUIPMENT	
Drag bar	Yes
Foldable handlebar	Yes
Horizontally adjustable handlebar	Yes
Plant guards	Optional
Rubber wheels	Included
Vertically adjustable handlebar	Yes
LUBRICANTS	
Fuel consumption	420 g/kWh
Power/fuel type	Petrol
Lubricant type (Engine)	SAE 30
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	23600 g
Paper	0 g
Paper + Cardboard total	4380 g
PE total	50 g
PET total	0 g
Plastic foil	50 g
Plastic rigid	0 g
Plastic total	50 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	740 mm
Packaging length	970 mm
Packaging width	640 mm
Quantity in Master pack	1
Article gross weight	120000 g
Article net weight	92000 g
Packaging volume	460 dm ³
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	99 dB(A)
Sound power level, measured	81.6 dB(A)
Sound pressure level at operators ear	81.6 dB(A)
EMISSION DATA EU	

ACCESSORIES



HUSQVARNA PADDY WHEEL KIT
536 62 51-01



HUSQVARNA METAL WHEEL KIT -
EMM
588 26 71-01



HUSQVARNA REAR TINE
ATTACHMENT
590 36 61-01



HUSQVARNA DITCHER
ATTACHMENT
590 36 59-01



HUSQVARNA WATER PUMP
589 52 72-02



HUSQVARNA SPRAYER
547 11 24-01